



# CB

**KEY FEATURES:**

- 80W with 8.6CFM forced air- cooling, 60W convection cooling
- 170 x 52 x 39 mm slim size with ATX output
- For both Medical and IT application
- PG/PF Signal
- +5V Stand by & Remote On/Off
- MTBF>130,000 hr. MIL-217F.

## 1. Description

The MATX-80U is a compact 170 x 52 x 39mm, ATX output power supply for medical embedded applications.

The device utilizes a thermally efficient U chassis design.

Output Voltage	Mini. Output Current	Rated Output Current	Max output Current <sup>(Note 1)</sup>	Line Regulation	Load Regulation	Ripple & Noise p-p <sup>(Note 2)</sup>	Initial Setting Accuracy <sup>(Note 3)</sup>
<b>+5V</b>	0.2A	5A	8A	1%	2%	50mV	5.08V to 5.13V
<b>+12V</b>	0A	1.5A	4A	1%	4%	120mV	11.4V to 12.6V
<b>-12V</b>	0A	0.5A		1%	5%	120mV	-11.4V to -12.6V
<b>+3.3V</b>	0A	4A	6A	1%	4%	50mV	3.10V to 3.50V
<b>+5Vsb</b>	0A	1A		1%	4%	120mV	4.80V to 5.20V

**Total Output Power:** 80W at 50°C environment temperature <sup>(Note 4)</sup>.

Note: 1) The maximum total combined output power on the +3.3V and +5V rails is 40W.

2) Measured by a 20MHz bandwidth limited oscilloscope when each output is connected with a 10µF Electrolytic Capacitor and a 0.1uF Ceramic Capacitor.

3) The +5V output is set between 5.08V to 5.13V by variable resistor and all output at 60% rated load and the other outputs are checked to be within the accuracy range.

4) Total maximum load cannot exceed 80W with 8.6 CFM forced air-cooling and 60W convection cooling.

5) With input voltage below 100V (90-99V), an accessory heat sink (min. 440 cm<sup>2</sup>) is recommend to be added at the bottom of the power supply.

## 2. Input Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Input Voltage	Continuous input range.	90	115/230	264	VAC
Input Frequency	AC input.	47		63	Hz
Hold Up Time	Nominal AC Input Voltage (230VAC), rated load.	20			ms
Input Current	Nominal AC Input Voltage (115VAC/230VAC), rated load.			2/1	A
Inrush Current	Nominal AC Input Voltage (115VAC/230VAC), one cycle at 25°C.			30/60	A
Input Protect	Non-user serviceable internally located AC input line fuse.				

## 3. Output Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Efficiency	Rated load, 115VAC. Varies with distribution of loads among output.		75		%
Minimum load			See Description		
Ripple & Noise	Rated load, 20MHz bandwidth		See Description		
Output Power	Continuous output power.		See Description		
Line Regulation	Less than ±1% at rated load with ±10% changing in input voltage.		See Description		
Load Regulation	Measuring is done by changing the output load +/-40% from 60% rated load, and keep other output at 60% rated load.		See Description		
Turn-on Delay	Time required for initial output voltage stabilization	0.3		4	Sec

#### 4. Interface Signals and Internal Protection

Parameter	Conditions/Description
Power On/Off	The power supply will be turned on when the power On/Off pin is connected to secondary GND.
Power Good Signal	When power is turned on, the power good signal will go high 100ms to 500ms after all output DC voltages are within regulation limits.
Power Fail Signal	The power fail signal will go low at least 1 mS before any of the output voltages fall below the regulation limits.
Over Voltage Protection	Built in over voltage protection circuit will auto-recover to prevent damaging external circuits. The trigger point is about 6.5-8.5V at +5V.
Over Load Protection	Fully protected against output overload and short circuit. Automatic recovery upon removal of overload condition.

#### 5. Safety Approvals, EMI and EMS Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Safety Approvals	UL, UL 60601-1, 2 <sup>nd</sup> edition				
	CB, IEC 60601-1				
	CB, IEC 60950-1				CB, IEC 60601-1 approved
	TUV, EN 60601-1, 2 <sup>nd</sup> edition				TUV, EN 60601-1 approved
	LVD, EN 60950-1				
Hi-Pot	Input to output	6173			VDC
Hold Up Time	Nominal AC Input Voltage (230VAC), rated load.	20			mS
Radiation	EN 60601-1-2	B			
Conduction	EN 55022 / CISPR 22 & FCC Part 15	B			Class
	EN 55022 / CISPR 22 & FCC Part 15	B			
EMS	IEC 61000-4-2, 8KV air discharge and 6KV contact discharge	3			
	IEC 61000-4-3, 3V/M	2			
	IEC 61000-4-4, 2KV line & PE	3			
	IEC 61000-4-5, 2KV	3			Level
	IEC 61000-4-6, 10V	3			
	IEC 61000-4-8, 10A/M	3			
IEC 61000-4-11	3				

#### 6. Environment Specification

Parameter	Conditions/Description	Min.	Nom.	Max.	Units
Operating Temperature	Derate linearly above 50°C by 2.5% per °C at 100% load:	0		50	°C
	to a maximum temperature of 70°C			70	
Storage Temperature		-40		+70	°C
Relative Humidity	Non-condensing.	5		95	%RH
Altitude	Operating			10K	Feet
	Non-operating			40K	

#### 7. Mechanical Specification

Parameter	Conditions/Description	
Dimension	170 x 52 x 39 mm, Tolerance +/- 0.4mm.	
Connector	CN1 --- AC input: Molex 5273-05A withdrew 2 pins or equivalent.	
	CN3 --- DC output: Molex 5273-12A or equivalent.	
	CN5 --- DC output: Molex 5045-03A.	
Pin Assignment	CN1 Pin 1. L 2. N 3. GND	
	CN3 Pin 1. 3.3V 2. 3.3V 3. GND 4. GND 5. GND 6. GND 7. +5V 8. +5V 9. +5V 10. PG/PF 11. +12V 12. -12V	
		CN5 Pin 1. +5Vsb 2. GND 3. PS on/off

◆ Dimension

170 x 52 x 39 mm (L x W x H)

